

Heat Detector



"Innovator in Gas Detection"

Model No. HD-6000

Heat Detector (HD-6000)



■ Feature

- * Available to connect with any fire control panel
- * High Reaction Speed with Alarm
(Red LED Lamp and Buzzer sound)

■ Products Information

Heat Detector (HD-6000)

Heat Detector

Model No. HD-6000



■ Specifications

Heat Detector (HD-6000)

| | |
|-----------------------|---------------------------|
| Sensor | Bimetal Sensor |
| Voltage | 10.8 to 13.2 V DC |
| Typical Alarm Current | 50 mA @ 12V DC |
| Operating Current | Maximum 25uA |
| Operating Temperature | -10`C ~ +50`C |
| Alarm Threshold | within 60 Seconds |
| Operating Indicator | Red LED |
| Output | Relay Contact |
| Operating Humidity | 85% RH |
| Case | Non-waterproof Type |
| Case Material | Poly Carbonate |
| Weight | approx. 127 gr |
| Dimension | 110 mm (diameter) x 39 mm |
| Installation | Wall Mounting Type |

Distributed by



G · E · T

Gas Detection Electronics Co., Ltd.

#1108, Daeryung Bldg., Mullaedong-5 ga,
Yeongdeungpo-gu, Seoul, 150-958, Korea

TEL : +82-2-6093-1910

FAX : +82-2-6093-1911

E-mail : info@gasdetection.co.kr

Website : www.gasdetection.co.kr